

BEST AVAILABLE COPY

WO 03/053736 A1



ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK,
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*

Device at a cargo support

5 The present invention relates to an arrangement for
a cargo support for trailers comprising connecting means for
the detachable attachment of the cargo support to a cargo
vehicle and a trailer of the kind in question, and means are
also provided for the detachable locking of the cargo support
10 to the deck of a vessel, in conjunction with which openings
in the cargo deck are provided to accommodate locking devices
that are arranged in the cargo support in question and are
capable of actuation causing them to be displaced from
locking engagement with the deck.

15 When trailers are transported on Ro-Ro vessels,
they must always as a rule be securely lashed to the deck in
such a way that they are unable to move even in heavy seas.
The accelerations to which the load is subjected can exceed 8
m/s², and the lashing means must accordingly be capable of
20 withstanding forces that are of the same order of magnitude
as the weight of the cargo.

 Handling of trailers in a port area usually takes
place in such a way that the tractor vehicles leave them at
and collect them from specially designated parking areas.
25 From here they are towed on board by special cargo handling
vehicles, known as tugmasters. The same tugmasters remove
trailers from the ship and take them to the parking area for
shipping.

 Trailers are provided with vertically adjustable
30 support legs, on which they stand on the quay. However, these
support legs are only designed to carry the vertical load
represented by the trailer's own weight.

 The support legs of the trailer are thus unable to
carry the loads which arise laterally and longitudinally as
35 the vessel pitches and rolls. This is why it is necessary,

when the trailer is on board, to support it with a cargo support in the form of a separate stand. The aforementioned stand has sufficient strength longitudinally and transversely. Previously disclosed technology for trailer
5 stands is as described below:

CONVENTIONAL TRAILER STAND. This cargo support is the original and, until now, the most common stand. It is always on board, and in principle it never leaves the ship.

Handling with such stands requires the tugmaster to
10 drive a trailer on board, after which one or two men manually pull out a stand and introduce it under the trailer, behind the tugmaster. The trailer is then lowered so that it is supported on the stand. The tugmaster can then be disconnected and driven away. The trailer is thus not
15 attached to the stand, but is only supported on it. The trailer is then lashed to the deck in accordance with the rules compiled for the respective vessel and sea route.

This system nevertheless requires space to be available for stands on board, and for the stands to be
20 stowed manually so that they do not obstruct the traffic during loading and unloading. It is also necessary for personnel and one stand to be ready at all times when the tugmaster arrives, if it is not to be kept waiting.

TRAILER STAND OF THE TOTE-LINE TYPE. This stand is
25 hooked securely to the king-pin of the trailer. The handling system is such that the stands can be "pre-loaded" on the trailers in their parking areas ashore, that is to say before the vessel arrives in the port.

The tugmaster is thus able to deliver the trailer
30 without the need for any personnel to be present in the immediate vicinity.

A certain amount of space must be provided on board, however, for unused stands. It is rarely the case that the number of trailers brought ashore corresponds precisely

to the number to be shipped out. In this case, the tugmaster is connected to the stand in question.

TRAILER STAND WITH REMOTELY CONTROLLED LOCKING

DEVICE. This stand exhibits an inverted U-shaped profile and
5 is provided with locking devices capable of being locked to the deck of the vessel in locking recesses.

Actuation of the aforementioned locking devices is performed from the cargo vehicle, and this involves complicated locking of the mechanism and transfer of the
10 actuating movement.

The principal object of the present invention is thus, in the first instance, to solve the aforementioned problems and to obtain cargo supports which, on the whole, function of their own accord without the need for additional
15 complicated locking arrangements.

The aforementioned object is achieved by means of an arrangement in accordance with the present invention, which is characterized essentially in that the aforementioned locking devices are so arranged as to be activated and
20 disconnected respectively through interaction between the cargo vehicle and the cargo support.

An arrangement executed in accordance with the invention constitutes a trailer stand with locking flaps. This support stand can also be pre-loaded on trailers before
25 the arrival of the vessel. The tugmaster collects a stand and introduces it under the trailer, in conjunction with which it is locked automatically to the trailer's king-pin.

The tugmaster drives on board and manoeuvres the trailer so that the legs of the stand are set down above the
30 openings for secure locking that are provided in the deck. The locking flaps then engage of their own accord in the locking position. When the tugmaster subsequently disengages and drives away, the actual locking takes place automatically by means of a locking bar falling down between the locking
35 flaps in such a way that they are prevented from moving.

This is effected by an operating arm on the stand being actuated by one or other part of the tugmaster, for example the turntable of the tugmaster. This actuating mechanism retains the locking bar in an upper, releasing
5 position for as long as the tugmaster is connected to the stand. When the tugmaster is not connected to the stand, the bar drops down and locks. Both locking to the deck and releasing from the deck thus take place entirely automatically.

10 The invention is described below with reference to the accompanying drawings, in which

Fig. 1 shows a trailer and a tractor vehicle during a connection phase;

15 Figs. 2-4 show the connection phase in greater detail viewed from the side of the tractor vehicle and the trailer and from its inside;

Fig. 5 shows a perspective view of the connection phase of a cargo support to the locking openings in the deck of a vessel;

20 Fig. 6 shows a sectioned view of the inside of a cargo stand during the lowering phase of the cargo support;

Fig. 7 shows a sectioned view of the inside of the aforementioned cargo support during the raising phase of the actual cargo support;

25 Figs. 8 and 9 show the interaction of a locking bar with the locking devices in the cargo support;

Fig. 10 shows the cargo support in the lowered and raised position;

30 Figs. 11-12 show a further illustrative embodiment of the invention, in conjunction with which

Fig. 11 shows a rotatable locking device viewed at an angle from below; and

35 Fig. 12 shows a perspective view seen at an angle from below of a cargo support in the raised position above openings capable of accommodating a locking device.

An arrangement 1 for a cargo support 2, which is executed as a stand and is intended to be used to support the front part 3A of a trailer 3 and comprises connecting means 4, 5, 6, 7 for the achievement of detachable attachment of the cargo support 2 to a cargo vehicle 8 and a trailer 3 of the kind in question and with means for the detachable locking of the cargo support to the deck 9 of a vessel, exhibits openings 11-14 in the cargo deck 9 arranged for the accommodation of locking devices 15, 16, 17 that are arranged in the cargo support 2 in question and are capable of actuation causing them to be displaced from locked engagement with the deck 9 of the vessel, comprises means such that the aforementioned locking devices 15-17 are so arranged as to be activated I and disconnected II automatically through interaction between the cargo vehicle 8 and the cargo support 2.

The aforementioned locking devices 15-17 are so arranged that, by lowering in a direction towards 18 and by setting down the cargo support 2 onto the deck 9 of the vessel, they are caused automatically to come into locking engagement III with associated subjacent lock accommodating openings 11-14, and that, in conjunction with the application of a lifting effect on the cargo support by means of the cargo support 2 and its associated lifting arm 19 with a connecting disc 7, they are caused to come out of engagement from locking interaction with associated subjacent lock accommodating openings 11-14.

The forces which an aforementioned trailer support stand 2 shall be capable of supporting are considerable, and the stand 2 shall be capable of absorbing forces of the order of 0.3 G in the fore-and-aft direction.

For the connection of a trailer 3 that is parked on its front support legs 21 on a base 22, a cargo vehicle 8 of the kind in question in the form of a so-called tugmaster can cause a cargo support 2 to be driven to the trailer 3 in the

area beneath its so-called king-pin 5. Different trailers can have different clearances beneath the trailer, depending on the type and depending on the height to which the driver has cranked up the trailer when leaving it. In many cases the
5 height is so low that the tugmaster is obliged to angle the cargo stand as shown in Fig. 1. In this case the legs of the trailer stand will drag along the ground, and there is a risk of damage to the locking mechanism.

It is necessary for the cargo support 2 to be
10 stable and to be capable of withstanding severe shocks. The cargo support 2 accordingly exhibits four pin-like strong bottom corner parts 23 tapering in the downward 18 direction and of matching shape to the lock openings 11-14 in question situated in the deck. Each bottom corner part 23 comprises a
15 suitable number of locking devices 15-17, each of which is formed by a jaw 25 pivotally mounted about a horizontal bearing shaft 24 in order to obtain locking interaction with a lock stop 26 in the aforementioned lock accommodating openings 11-14, more specifically so that the locking device
20 15-17 is formed by a recess 27 adapted to accommodate one edge 26A of an aforementioned lock stop 26, which extends along the respective lock accommodating opening 11-14.

The aforementioned locking devices 15-17 are so arranged as to be actuated jointly by a separate internal
25 frame 29 capable of displacement relative to the outer supporting part 28 of the cargo support. The aforementioned moving frame 29 is in turn capable of actuation by, for example, the connecting disc 7 or some other part of a cargo vehicle 8 when a cargo vehicle 8 of the kind in question
30 intended for connection passes, for example, through the aforementioned cargo support.

As illustrated in the drawings in Figs. 2-4, a mechanism 30 which comprises an articulated link between the
aforementioned frame 29 and a pivotally supported pivot arm
35 31 capable of actuation can be so arranged as to transmit

movement from the cargo vehicle 8 to the aforementioned frame 29 after actuation by means of, for example, its connecting disc, etc., 7. In the aforementioned actuating position, when the cargo vehicle 8 is close to the cargo support 2 and these
5 are connected to one another, the frame 29 is held in a raised position away from the locking devices 15-18.

It is also possible by means of a lifting tool, for example with a simple lifting rod, for example a crowbar, to raise the aforementioned frame 29 manually in a direction
10 away from 32 the deck 9 of the vessel if the need arises.

The aforementioned frame 29 forms a transverse horizontal bar 33 at its lower end 29A for the purpose of enabling it to be locked together with the bar through the effect of the own weight of the frame.

15 The number of locking devices 15-17 can be varied, but it is expedient to arrange two or three locking devices accommodated in the respective bottom corner part 23 and facing one another when viewed from the side.

In accordance with a further illustrative
20 embodiment, which is shown in Figs. 11-12, the aforementioned locking devices 150 are so arranged as to be capable of actuation by spring force 151 causing them to be displaced into locked engagement with associated subjacent lock accommodating openings 152 of matching form with the help of
25 a spring mechanism 153. The aforementioned spring mechanism 153 is capable of activation when a cargo vehicle in question passes the mechanism and actuates a catch 154 and the aforementioned locking devices 150 are so arranged as to be released when the cargo vehicle in question once more comes
30 into position beneath the cargo support 102.

The principle of the first-mentioned illustrative embodiment of the arrangement in accordance with the invention respectively for opening and closing the locking function of the cargo support may be simplified as follows:

When the stand is set down, the upper claw 34 of the respective locking device 15-17 engages with the upper side 9A of the deck 9, while the lower claw 35 is accommodated in it as a so-called lash pot, i.e. a lock recess executed as the lock accommodating opening 11-14 through and under the deck 9. The mechanism is caused in this way to rotate in the direction of the arrow 36 about the pivot axle 24, so that the jaw 25 in its entirety eventually grips around the edge of the hole in the deck or some other functioning lock stop 26 in the respective lock accommodating opening 11-14 for each group of lock devices 15-17. Use is made for this purpose of the weight of the trailer 3 supported above the cargo support 2 as a help in conjunction with locking. Fig. 6 shows this clearly.

When the cargo vehicle 8 has again driven up to the cargo support 2 and raises it, the lower claw 35 takes hold of the under side 9B of the deck plate 9 and forces the mechanism to open by degrees, and when the locking device 15-17 has rotated in the direction of the arrow 37 as far as its end position, the cargo support 2 is free to be raised from the deck 9. In conjunction with this, the lifting power of the cargo vehicle 8 was used to unlock the mechanism.

The invention in accordance with the invention also exhibits the following functions:

The arrangement is forced into the open position II by the force with which the cargo vehicle 8 is able to lift the cargo support 2.

The arrangement is brought into the locking position I by the effect of gravity of the cargo support 2 and the part 3A of the trailer 3 resting on it.

The arrangement is locked in the locked position I by a bar 33, which falls down due to its own weight between the locking devices 15-17 and then rests against a stop 38 thereon once the cargo vehicle has been disconnected and has moved away from the parking position on board.

The aforementioned locking bar 33 is forced up into the releasing position by the cargo vehicle 8 when it is connected to the cargo support 2. An indicating flag or other signal can be connected to the locking bar 33 in order to be
5 able to indicate from a distance when the locking bar 33 is in its lower locked position. The aforementioned indicating flag need not indicate when the locking bar 33 is in its raised disconnected position.

The aforementioned locking bar 33 can also be
10 lifted up or pushed down manually from the outside, if the need arises, for example with the help of a crowbar or some other actuating means.

The attachment frame 29 of the locking arrangement is capable of displacement together with the bar 33 in the
15 vertical sense in relation to other parts of the cargo support 2.

The attachment frame 29 of the locking arrangement is so arranged as to enclose the locking devices 15-17 in a direction from the front, from the rear and below so that it
20 forms a guard for the locking devices 15-17.

The self-locking mechanism illustrated in Figs. 11-12 for locking each of the locking devices 150 to its own lock opening 152 of matching form functions in such a way that the locking devices 150 are capable of actuation when a
25 cargo vehicle of the kind in question exits from the cargo support 102 in question or is removed in some other way from a mechanism 153 of the kind in question, and that the locking devices 150 are so arranged as to be disengaged when the cargo vehicle in question again reaches the mechanism 153 in
30 the cargo support 102 in question. The mechanism 153 comprises pairs of pulley wheels 155, 156, each of which is supported by its own shaft 157, 158, on which assembled, combined compression and torsion springs 159, 160 sit. An aforementioned locking device 150 is connected to each of the
35 shafts 157, 158 in such a way that they are capable of being

rotated together. A cable 161 passes around each of the guide rollers 162 and continues to the aforementioned pulley wheels 155, 156 with its divided line ends 161A, 161B. The opposite end 161C of the cable 161 is attached to a lever arm 163 that
5 is rigidly connected to a rotating shaft 164. This shaft 164 is rigidly attached to the actuatable catch 154, which is rotatably mounted internally in the upper horizontal frame 165 of the cargo support. The catch is capable of being rotated out through an opening 166 against the effect of a
10 spring force exerted by the springs 159, 160 and is laterally displaced from the so-called kingpin of the cargo support, i.e. the connection 6 to which the connection 7 of the cargo vehicle 7 is connected.

The locking devices 150 are actuated, when in the
15 locked position, by the springs 159, 160, which are arranged transversely as illustrated in Fig. 12, and each spring is thus accommodated in a recess 152 of matching form, as illustrated in Fig. 11, securely retained at a mutual distance from one another in the interests of clarity.

20 After spring-assisted actuation of the engagement arm 154 that is capable of rotating together with the shaft 164, after the vehicle has exited from the space 167 under the cargo support 102, the locking devices 150 are caused to rotate in the direction of the arrow 168 until these arrive
25 in a position in which they can be drawn up out of the associated recess 152, i.e. ca. 90° from the locked position.

The locking function is thus achieved through the movement of the cargo vehicle and actuation of the cargo support, in conjunction with which the assembly as a whole is
30 brought into the locked position by the cargo vehicle, and is also opened after actuation by the cargo vehicle.

The invention is naturally not restricted to the embodiments described above and illustrated in the accompanying drawings. Modifications are possible, in
35 particular in respect of the nature of the different

component parts, or by the use of equivalent technology, without departing from the area of protection afforded to the invention, as defined in the Patent Claims.

P a t e n t C l a i m s

- 5 1. Arrangement (1) for a cargo support (2) for
trailers comprising connecting means (4-7) for the detachable
attachment of the cargo support (2) to a cargo vehicle (8)
and a trailer (3) of the kind in question, and means are also
provided for the detachable locking of the cargo support to
10 the deck of a vessel, in conjunction with which openings (11-
14) in the cargo deck (9) are provided to accommodate locking
devices (15-17) that are arranged in the cargo support (2) in
question and are capable of actuation causing them to be
displaced from locking engagement with the deck (9),
15 **characterized in that** the aforementioned locking devices (15-
17; 150) are so arranged as to be activated and disconnected
respectively through interaction between the cargo vehicle
(8) and the cargo support (2).
2. Arrangement in accordance with Patent Claim 1,
20 **characterized in that** the aforementioned locking devices
(15-17) are so arranged that, by lowering in a direction
towards (18) and by lowering of the cargo support (2) onto
the deck (9) of the vessel, they are caused automatically to
come into locking engagement with associated subjacent lock
25 accommodating openings (11-14), and that, in conjunction with
the application of a lifting effect on the cargo support (2),
they come out of engagement from the locking interaction with
associated subjacent lock accommodating openings (11-14).
3. Arrangement in accordance with Patent Claim 2,
30 **characterized in that** the locking devices (15-17) are formed
by pivotally mounted jaws 25 in order to obtain locking
interaction with a lock stop (26) in the associated subjacent
lock accommodating openings (11-14).

4. Arrangement in accordance with Patent Claim 3,
characterized in that the locking device (15-17) is formed by
a recess (27) adapted to accommodate one edge (26A) of a lock
stop (26), which extends along the lock accommodating opening
5 (11-14).

5. Arrangement in accordance with one or other of
Patent Claims 2-4, *characterized in that* the locking devices
(15-17) are so arranged as to be actuated jointly by a
separate mobile frame (29) relative to the outer supporting
10 part (28) of the cargo support, which is in turn capable of
actuation by, for example, the connecting disc (7) or some
other part of a cargo vehicle when a cargo vehicle (8) of the
kind in question passes in under the aforementioned cargo
support (2).

15 6. Arrangement in accordance with Patent Claim 5,
characterized in that the aforementioned frame (29) is so
arranged as to be capable of actuation manually by means of a
lifting tool, for example a lifting arm in the form of a
crowbar, to raise it in a direction away from (32) the deck
20 (9) of the vessel, if necessary.

7. Arrangement in accordance with one or other of
Patent Claims 5-6, *characterized in that* the aforementioned
locking devices are capable of actuation by a bar (33)
included in the aforementioned frame (29) to be locked
25 together.




8. Arrangement in accordance with one or other of
Patent Claims 5-7, *characterized in that* the cargo support
(2) exhibits pin-like bottom corner parts (23) tapering in
the downward (18) direction and adjacent to the lock openings
30 (11-14) in question of matching form situated in the deck.

9. Arrangement in accordance with Patent Claim 8,
characterized in that the mutually opposing locking devices
(15-17) are arranged in each bottom corner part (23).


10. Arrangement in accordance with Patent Claim 1,
35 *characterized in that* the aforementioned locking devices

(150) are so arranged as to be capable of actuation by spring force (151) causing them to be displaced into locked engagement with associated subjacent lock accommodating openings (152) with the help of a spring mechanism (153),
5 which is capable of activation when a cargo vehicle in question moves out from the cargo support or is removed from a mechanism (153) of the kind in question in some other way, and in that the aforementioned locking devices (150) are so arranged as to be released when the cargo vehicle in question
10 once more reaches the mechanism (153) in the cargo support (102) in question.



2 / 7





3 / 7



4 / 7



5 / 7



6 / 7

FIG.11






FIG.10



7/7



INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 02/02076

A. CLASSIFICATION OF SUBJECT MATTER

IPC7: B60P 7/13

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC7: B60P, B65G, B62D, B63B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

SE,DK,FI,NO classes as above

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

EPO-INTERNAL, WPI DATA, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	NO 153091 B (GUNVALD M S BERGER), 23 July 1979 (23.07.79), page 1, line 19, figures 1,5, claim 1 --	1-10
A	SE 446330 B (NILS S E LARSSON ET AL), 1 Sept 1986 (01.09.86), figures 3a,3b, abstract --	1,2,5,8,9
A	US 5570981 A (BREWSTER), 5 November 1996 (05.11.96), figures 4-10, abstract --	1,3,4,10
A	US 5613814 A (JACKSON), 25 March 1997 (25.03.97), figure 2, abstract --	1,3,4,10

☒ Further documents are listed in the continuation of Box C.
 ☒ See patent family annex.

* Special categories of cited documents	"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
"A" document defining the general state of the art which is not considered to be of particular relevance	"X" document of particular relevance: the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
"E" earlier application or patent but published on or after the international filing date	"Y" document of particular relevance: the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	"&" document member of the same patent family
"O" document referring to an oral disclosure, use, exhibition or other means	
"P" document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search	Date of mailing of the international search report
6 February 2003	06-03-2003
Name and mailing address of the ISA/ Swedish Patent Office Box 5055, S-102 42 STOCKHOLM Facsimile No. +46 8 666 02 86	Authorized officer Alexandra Jarlmark/EK Telephone No. +46 8 782 25 00

INTERNATIONAL SEARCH REPORT

International application No.

PCT/SE 02/02076

C (Continuation). DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 2543295 A (A D MCGREGOR ET AL), 27 February 1951 (27.02.51), figures 1-7 --	1
A	SE 419072 B (KALMAR LAGAB AB), 13 July 1981 (13.07.81), page 1, line 1 - page 2, line 8, figures 1,2 -- -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

30/12/02

International application No.

PCT/SE 02/02076

Patent document cited in search report			Publication date	Patent family member(s)	Publication date
NO	153091	B	23/07/79	NO 790159 A	23/07/79
SE	446330	B	01/09/86	SE 8304440 A	18/02/85
US	5570981	A	05/11/96	CA 2133933 A	17/05/95
US	5613814	A	25/03/97	NONE	
US	2543295	A	27/02/51	NONE	
SE	419072	B	13/07/81	BE 875514 A	31/07/79
				CA 1122481 A	27/04/82
				DE 2914718 A,C	31/10/79
				DK 145379 A	19/10/79
				DK 155153 B,C	20/02/89
				FI 74660 B,C	30/11/87
				FI 791133 A	19/10/79
				FR 2423429 A,B	16/11/79
				GB 2018725 A,B	24/10/79
				NL 187528 B,C	03/06/91
				NL 7903014 A	22/10/79
				NO 152331 B,C	03/06/85
				NO 791200 A	19/10/79
				SE 7804359 A	19/10/79

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.